



ENERG
енергия · ενεργεια



WPE-I 07.1 Plus H 230

STIEBEL ELTRON



55 °C

35 °C



A+++

A+++



38 dB



0 dB

■ 6
■ 6
■ 6

kW

■ 7
■ 7
■ 7

kW



2019

811/2013

Product datasheet: Required details about space heater with heat pump to Regulation (EU) No 813/2013 & 811/2013 / (S.I. 2019 No. 539 / Programme 2)

		WPE-I 07.1 Plus H 230
		207183
Manufacturer		STIEBEL ELTRON
Space heating energy efficiency class under average climate conditions, medium-temperature applications (A+++ -> D)		A+++
Energy efficiency class, space heating under average climate conditions, low-temperature applications (A+++ -> D)		A+++
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	6
Rated heating output under average climate conditions for low-temperature applications (P rated)	kW	7
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η_s)	%	154
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	200
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	3271
Annual energy consumption under average climate conditions for low-temperature applications (QHE)	kWh/a	2785
Sound power level, indoor	dB(A)	38
Option for operation only at off-peak times		-
Special measures		Alle beim Zusammenbau, der Installation oder Wartung des Raumheizgerätes zu treffenden besonderen Vorkehrungen: Siehe Installations- und Montageanweisung
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	6
Rated heating output under colder climate conditions for low-temperature applications (P rated)	kW	7
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	6
Rated heating output under warmer climate conditions for low-temperature applications (P rated)	kW	7
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η_s)	%	157
Seasonal space heating energy efficiency under colder climate conditions for low-temperature applications (η_s)	%	210
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η_s)	%	157
Seasonal space heating energy efficiency under warmer climate conditions for low-temperature applications (η_s)	%	203
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	3828
Annual energy consumption under colder climate conditions for low-temperature applications (QHE)	kWh/a	3168
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	2083
Annual energy consumption under warmer climate conditions for low-temperature applications (QHE)	kWh/a	1777
Sound power level, outdoor	dB(A)	0



ENERG

енергия · ενεργεια



WPE-I 07.1 Plus H 230

STIEBEL ELTRON



A⁺⁺⁺

A⁺⁺⁺

A⁺⁺

A⁺

A

B

C

D

E

F

G

A⁺⁺⁺

+



+



+



+



Product datasheet: Required details about space heater with heat pump to Regulation (EU) No 813/2013 & 811/2013 / (S.I. 2019 No. 539 / Programme 2)

		WPE-I 07.1 Plus H 230
		207183
Manufacturer		STIEBEL ELTRON
Seasonal space heating energy efficiency under average climate conditions for low-temperature applications (η_s)	%	200
Temperature control class		II
Contribution of temperature control to space heating energy efficiency	%	2
Space heating energy efficiency of package under average climate conditions	%	157
Space heating energy efficiency of package under colder climate conditions	%	160
Space heating energy efficiency of package under warmer climate conditions	%	160
Value of differential between space heating energy efficiency under average climate conditions and that under colder climate conditions	%	3
Value of differential between space heating energy efficiency under warmer climate conditions and that under average climate conditions	%	3
Energy efficiency class, space heating under average climate conditions, low-temperature applications (A+++ -> D)		A+++
Space heating energy efficiency class of package under average climate conditions (A+++ -> D)		A+++

Product datasheet: Required details about space heater with heat pump to Regulation (EU) No 813/2013 & 811/2013 / (S.I. 2019 No. 539 / Programme 2)

		WPE-I 07.1 Plus H 230
		207183
Manufacturer		STIEBEL ELTRON
Heat source		Sole
Low temperature heat pump		-
With auxiliary heater		x
Combination heater with heat pump		x
Rated heating output under colder climate conditions for medium-temperature applications (P rated)	kW	6
Rated heating output under average climate conditions for medium-temperature applications (P rated)	kW	6
Rated heating output under warmer climate conditions for medium-temperature applications (P rated)	kW	6
T _j = -7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	3.9
T _j = -7 °C heating output, partial load range under average climate conditions (Pdh)	kW	5.7
T _j = 2 °C heating output, partial load range under colder climate conditions (Pdh)	kW	2.4
T _j = 2 °C heating output, partial load range under average climate conditions (Pdh)	kW	3.5
T _j = 2 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	6.4
T _j = 7 °C heating output, partial load range under colder climate conditions (Pdh)	kW	2.0
T _j = 7 °C heating output, partial load range under average climate conditions (Pdh)	kW	2.2
T _j = 7 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	4.1
T _j = 12 °C heating output, partial load range under colder climate conditions (Pdh)	kW	2.0
T _j = 12 °C heating output, partial load range under average climate conditions (Pdh)	kW	2.0
T _j = 12 °C heating output, partial load range under warmer climate conditions (Pdh)	kW	1.8
T _j = dual mode temperature under colder climate conditions (Pdh)	kW	6.4
T _j = dual mode temperature under average climate conditions (Pdh)	kW	6.4
T _j = dual mode temperature under warmer climate conditions (Pdh)	kW	6.4
T _j = operating temperature limit under colder climate conditions (Pdh)	kW	6.4
T _j = operating temperature limit under average climate conditions (Pdh)	kW	6.4
T _j = operating temperature limit under warmer climate conditions (Pdh)	kW	6.4
For air source heat pumps: T _j = -15 °C (if TOL < -20 °C) (Pdh)		-
Dual mode temperature under colder climate conditions (Tbiv)	Grad C	-22
Dual mode temperature under average climate conditions (Tbiv)	Grad C	-10
Dual mode temperature under warmer climate conditions (Tbiv)	Grad C	2
Seasonal space heating energy efficiency under colder climate conditions for medium-temperature applications (η _s)	%	157
Seasonal space heating energy efficiency under average climate conditions for medium-temperature applications (η _s)	%	154
Seasonal space heating energy efficiency under warmer climate conditions for medium-temperature applications (η _s)	%	157
T _j = -7 °C COP, partial load range under colder climate conditions (COPd)		3.82
T _j = -7 °C COP, partial load range under average climate conditions (COPd)		3.10
T _j = 2 °C COP, partial load range under colder climate conditions (COPd)		4.36
T _j = 2 °C COP, partial load range under average climate conditions (COPd)		4.09
T _j = 2 °C COP, partial load range under warmer climate conditions (COPd)		2.82
T _j = 7 °C COP, partial load range under colder climate conditions (COPd)		5.63
T _j = 7 °C COP, partial load range under average climate conditions (COPd)		4.73

Tj = 7 °C COP, partial load range under warmer climate conditions (COPd)		3.65
Tj = 12 °C COP, partial load range under colder climate conditions (COPd)		5.69
Tj = 12 °C COP, partial load range under average climate conditions (COPd)		5.61
Tj = 12 °C COP, partial load range under warmer climate conditions (COPd)		5.21
Tj = dual mode temperature under colder climate conditions (COPd)		2.82
Tj = dual mode temperature under average climate conditions (COPd)		2.82
Tj = dual mode temperature under warmer climate conditions (COPd)		2.82
Tj = operating temperature limit under colder climate conditions (COPd)		2.82
Tj = operating temperature limit under average climate conditions (COPd)		2.82
Tj = operating temperature limit under warmer climate conditions (COPd)		2.82
For air source heat pumps: Tj = -15 °C (if TOL < -20 °C) (COPd)		-
Operating temperature limit under colder climate conditions (TOL)	Grad C	-22
Operating temperature limit under average climate conditions (TOL)	Grad C	-10
Operating temperature limit under warmer climate conditions (TOL)	Grad C	2
Operating temperature limit of heating water under colder climate conditions (WTOL)	Grad C	70
Operating temperature limit of heating water under average climate conditions (WTOL)	Grad C	70
Operating temperature limit of heating water under warmer climate conditions (WTOL)	Grad C	70
Power consumption, off-mode (Poff)	Watt	17
Power consumption, thermostat off-mode (PTO)	Watt	19
Power consumption, standby state (PSB)	Watt	17
Power consumption, operating state, with crankcase heating (PCK)	Watt	0
Rated heating output of auxiliary heater under colder climate conditions (PSUP)	kW	0.0
Rated heating output of auxiliary heater under average climate conditions (PSUP)	kW	0.0
Rated heating output of auxiliary heater under warmer climate conditions (PSUP)	kW	0.0
Type of energy supply, auxiliary heater		elektrisch
Output control		veränderlich
Sound power level, outdoor	dB(A)	0
Sound power level, indoor	dB(A)	38
Annual energy consumption under colder climate conditions for medium-temperature applications (QHE)	kWh/a	3828
Annual energy consumption under average climate conditions for medium-temperature applications (QHE)	kWh/a	3271
Annual energy consumption under warmer climate conditions for medium-temperature applications (QHE)	kWh/a	2083
Flow rate on heat source side	m3/h	1
Special measures	Alle beim Zusammenbau, der Installation oder Wartung des Raumheizgerätes zu treffenden besonderen Vorkehrungen: Siehe Installation- und Montageanweisung	